

| | | |
|---------------------|------|-----|
| CI/SfB | (43) | Yr4 |
| CAW M40 | | |
| Uniclass L553:P7103 | | |
| June 2008 | | |

Epoxy Grout Ex-1

High Strength, Free Flowing Epoxy Grout

KEY BENEFITS SUMMARY

- High strength
- Good chemical and oil resistance
- Tolerant of severe vibrations

PRODUCT INFORMATION

Description

Tremco Epoxy Grout Ex-1 is a high strength grout developed specifically for a range of heavy duty applications. It has good chemical and oil resistance, and bonds well to steel, concrete and other dry surfaces.

Typical Uses

Ideal for fixing bearing plates for cranes, generators, vibrating machinery, compressors, starter bars and fixings. Use specifically where severe vibration may be encountered or chemical resistance is important.

Packaging

20 kg (3 component kit)

Colour

Natural / beige



Coverage Rate

A 20 kg unit when mixed produces approximately 10 litres of product. For calculation purposes use the formula: $\text{volume (m}^3\text{)} \times 100 = \text{number of 20 kg units required}$ i.e. 1 cubic metre = 100 x 20 kg units.

Cure Time

Working time: Approx 15 minutes

Storage

Store in dry shaded conditions between +5°C and +25°C.

Shelf Life

12 months when stored as recommended in original unopened packaging.

Health & Safety Precautions

Product Health and Safety Data Sheets must be read and understood before use.

USAGE GUIDELINES

The substrate should be clean, dry and free from oil, and contaminants and any shuttering should be sealed and of good strength to prevent deformation. Mix the resin and curing agent using a spatula or similar blade or bar. Immediately add the supplied aggregate until the desired consistency is achieved and apply by pouring.

TREMCO

Epoxy Grout Ex-1

Tremco illbruck Limited
Coupland Road
Hindley Green, Wigan WN2 4HT UK
Tel: 01942 251400
Fax: 01942 251410
Email: info@tremco-illbruck.co.uk
Website: www.tremco-illbruck.com

Technical Service

Tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco illbruck written instructions and (b) in any application recommended by Tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.