

CI/SfB	(43)	Yr4
CAW M40		
Uniclass L553:P213		
June 2008		

Epoxy Mortar - Rapid Set

Rapid Set Epoxy Mortar

KEY BENEFITS SUMMARY

- Developed specifically for fast-track repairs
- Trafficable after 3 hours

PRODUCT INFORMATION

Description

Tremco Epoxy Mortar - Rapid Set is a resin rich blend of specially selected finely graded aggregate and epoxy resin.

Typical Uses

Ideal for fast-track repairs of heavy-duty industrial areas. Can be opened to heavy traffic after just 3 hours.

Packaging

25 kg (2 component kit)

Colour

Grey

Storage

Store in dry shaded conditions between 10°C and +25°C.

Shelf Life

9 months when stored as recommended in original unopened packaging.

Coverage Rate

Approx. 3 m² per 25 kg at 5 mm thick



Curing Time

3 hours @ 20°C

6 hours @ 10 - 15 °C

Health & Safety Precautions

All Health and Safety Data Sheets must be read and understood before use.

USAGE GUIDELINES

Surface Preparation

Surfaces should be clean, dry and free of all loose material. Wire brushing or sweeping is generally sufficient. Use Tremco Degreaser to remove grease and oil.

Priming

A primer is not usually required if patch or crack repairing. Use Treadfast ES 3000 if using as a thin section screed or when applying to smooth, non-porous or metal surfaces.

Mixing

Each unit of Tremco Epoxy Mortar - Rapid Set contains a granular resin and separate containers of curing agent. The components are mixed with a trowel according to the simple instructions on the pack until a smooth grey mortar is obtained. The more thorough the mixing, the 'wetter', smoother and more manageable the mix becomes. This can be achieved quite quickly by wearing disposable gloves and kneading the mixture by hand. A cretriangle or similar mixer can be used to ensure thorough mixing of larger quantities.

TREMCO

Epoxy Mortar - Rapid Set

Tremco illbruck Limited
Coupland Road
Hindley Green, Wigan WN2 4HT UK
Tel: 01942 251400
Fax: 01942 251410
Email: info@tremco-illbruck.co.uk
Website: www.tremco-illbruck.com

Application

Tremco Epoxy Mortar - Rapid Set is trowelled firmly against the surface to be repaired, and finished with a trowel or float. To prevent drag on the trowel, a rag moistened with white spirit may be wiped across the face of the tool.

Technical Service

Tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco illbruck written instructions and (b) in any application recommended by Tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.