

## SAFETY DATA SHEET

### EPOXY MORTAR DEEP FILL EPOXY COMPONENT

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	EPOXY MORTAR DEEP FILL EPOXY COMPONENT
PRODUCT NO.	10823
APPLICATION	Resin component of a two-part epoxy floor repair mortar
SUPPLIER	Tremco illbruck Production Ltd Coupland Rd Hindley Green Wigan WN2 4HT England +44 (0) 1942 258011 msds@tremco-illbruck.co.uk
CONTACT PERSON	R P Brisbourne
EMERGENCY TELEPHONE	(+44) 1942 258011

#### 2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact.

Irritating to eyes and skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. R52/53.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
EPOXY RESIN (Number average MW <= 700 )	500-033-5	25068-38-6	5-10%	R43 Xi;R36/38 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INGESTION

DO NOT INDUCE VOMITING! Immediately rinse mouth and provide fresh air. Get medical attention immediately!

##### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

##### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Fire can be extinguished using:

Water spray, fog or mist.

Foam.

Powder.

# EPOXY MORTAR DEEP FILL EPOXY COMPONENT

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Persons susceptible for allergic reactions should not handle this product.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT



### HAND PROTECTION

Use protective gloves.

### EYE PROTECTION

Wear approved safety goggles.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Granular		
COLOUR	Buff		
ODOUR	Almost odourless		
SOLUBILITY	Immiscible with water		
BOILING POINT (°C)	> 200	RELATIVE DENSITY	> 2
FLASH POINT (°C)	> 150°	VOLATILE ORGANIC COMPOUND (VOC)	0 g/litre

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### HAZARDOUS DECOMPOSITION PRODUCTS

High temperatures generate: Toxic gases/vapours/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## 11 TOXICOLOGICAL INFORMATION

### SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact.

### EYE CONTACT

Irritating to eyes.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Dangerous for the environment: Degrades very slowly in nature.

# EPOXY MORTAR DEEP FILL EPOXY COMPONENT

## BIOACCUMULATION

Medium potential for bioaccumulation

## DEGRADABILITY

Rapid hydrolysis in soil or water followed by slow biodegradation

## ACUTE FISH TOXICITY

High toxicity to aquatic organisms

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Waste product is classified as Hazardous Waste

Mixed, fully cured product is not classified as hazardous

Contaminated rags etc are also hazardous waste, as are uncleaned cans.

### DISPOSAL METHODS

In the UK refer to the Hazardous Waste Regulations (2005)

### WASTE CLASS

EWC Code: 08 04 09 Hazard Classification: H4

## 14 TRANSPORT INFORMATION

### GENERAL

Not regulated.

## 15 REGULATORY INFORMATION

### LABELLING



Irritant

### CONTAINS

EPOXY RESIN (Number average MW <= 700 )

### RISK PHRASES

- |        |   |
|--------|---|
| R43    | May cause sensitisation by skin contact.  |
| R36/38 | Irritating to eyes and skin.  |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

### SAFETY PHRASES

- |        |   |
|--------|---|
| S26    | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S37    | Wear suitable gloves.   |
| S24/25 | Avoid contact with skin and eyes.   |
| P5     | Contains epoxy constituents. See information supplied by the manufacturer.                    |

### UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging for Supply) Regulations 2002

Chemicals (Hazard Information and Packaging for Supply) (Amendment) Regulations 2005 (CHIP 3.1)

### EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC

## 16 OTHER INFORMATION

### REVISION DATE

05/06/2008

# EPOXY MORTAR DEEP FILL EPOXY COMPONENT

## RISK PHRASES IN FULL

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.