



ACM Asphalt Paint

A solvent free paint for internal and external asphalt and bitumen surfaces

ACM Asphalt Paint is the ideal way to seal, protect and colour asphalt and similar surfaces. The thick, flexible coating is easy to apply by brush or roller and is available in a range of attractive colours.

ACM Asphalt Paint is ideal for use in warehouses, plant rooms, asphalt walkways on roofs, car park bays and for line marking on tennis courts, playgrounds etc.

APPEARANCE

Coloured, low to mid sheen finish depending upon substrate and number of coats applied.

COVERAGE

5 litres covers 20-30m² per coat depending on the texture of the substrate. One coat normally required. The coverage rate does not allow for filling the crevices and texture of a tarmac or asphalt surface. Using the product in this way will greatly reduce coverage and extend drying time.

SHELF LIFE

At least one year in manufacturer's unopened containers.

STORAGE

Store in cool, dry conditions away from direct sunlight.

SURFACE PREPARATION

ACM Asphalt Paint can be applied to asphalt, tarmac, porous concrete, masonry, bricks, breeze blocks and most metals. Ensure the surface is clean, sound and dry (slightly damp is acceptable). ACM Asphalt Paint can be applied to existing paint providing all poorly bonded material is removed and glossy surfaces are dulled using abrasive paper.



APPLICATION

Apply ACM Asphalt Paint by brush or medium pile type roller. One coat is generally sufficient although a second coat may be required on very porous or very rough surfaces. Avoid applying too thickly. Do not apply externally if rain or frost is forecast or if the temperature is below 10°C. The second coat should be applied after approximately 1 hour.

COLOURS AVAILABLE

White, Tile Red, Green, Light Blue, Light Grey, Black

CURING TIME

The product will cure sufficiently in approximately 24 hours to accept light traffic, but allow 48 hours before bringing the area back into full use. Cold, damp or humid weather will delay curing.

CLEANING OF APPLICATORS

Clean applicators in warm soapy water before the product has started to cure.

HEALTH & SAFETY

Contact ACM for details



Advanced
Construction
Materials Ltd



ISO 9001 quality standard
for manufacture & supply

The Heath Business and Technical Park, Runcorn WA7 4QX Telephone: 01928 515787 Facsimile: 01928 515791 www.acml.co.uk

IMPORTANT NOTE

The information contained in this Data Sheet is based on tests believed to be reliable, practical experience and is published in good faith. However because we have no control over the application conditions we do not guarantee the results obtained. Responsibility for establishing suitability of the product rests with the purchaser. No liability or claim for damage or consequential loss is accepted from the use of this product. Whilst every effort has been made to ensure the information is correct at the time of publication it is the responsibility of the user to ensure that the product is suitable for the particular installation.

Please note that the mix design shown for sand, cement and granite is for indication purposes only and does not serve as a specification. Suitability of the mix design for a particular project is down to the installer.