



ACM Surefoot

EPOXY BASED SAFETY FLOORING FOR INDUSTRY

A lightly textured epoxy resin roller applied treatment which withstands regular fork lift trucks and other industrial usage in general factory areas. Slip hazard is considerably reduced. Solvent free, very low odour formation.

ADVANTAGES

ACM Surefoot greatly increases grip for pedestrians and vehicles. Chemical resistance is good and the tough epoxy resin ensures durability. An attractive matt finish is provided.

The aggregate is already incorporated into the coating, thus greatly reducing the problems that can be encountered when scattering, as a generally even texture is achieved.

SURFACE PREPARATION

Subfloor preparation is of key importance with products of this nature. The surface should be free of oil and grease. Weak material or laitence should be removed prior to application of the product. Highly polished surfaces e.g. powerfloated concrete, marble and terrazzo tiles should be mechanically textured. The floor should then be either vacuumed or swept clean. Sound, stable floor construction is essential.

APPLICATION PROCEDURE

Thoroughly mix the two liquid components of the **ACM Surefoot** pack. We recommend the use of a slow speed drill and stirrer attachment (available from **ACM** if required). Spatulas or other square edged implements are acceptable if used diligently. Apply by roller. The second coat should be applied when the first coat has cured (usually overnight).

PACK SIZE/ COVERAGE

5L packs, coverage approximately 30sq.m. Two coats are usually applied.



CURING

Within 24 hours at normal temperature.

CLEANING

Brush or scrubbing machine fitted with fine bristle heads.

COLOURS AVAILABLE

Light grey, mid grey, tile red, buff, mid blue and mid green.

HEALTH AND SAFETY

Information supplied upon request.

CONTRACT APPLICATION

A network of approved independent installers is established for contract application. Please contact **ACM** for details.

TECHNICAL SERVICE

A full application and advisory service is available.

IMPORTANT: Store in reasonably warm areas. Use **ACM Epoxy Slip Grip** for fire escapes, ramps, and other areas where aggressive slip resistance is required.

The above information serves as guidelines only. Since the work with the product is beyond our control, our responsibility is limited to the product only.

The Heath Business & Technical Park, Runcorn, Cheshire, WA7 4QX Telephone: 01928 515787 Facsimile: 01928 515791 www.acml.co.uk

